

MARSCHNER-LAGERTRAFO-PROGRAMM

Range available ex stock



Typ/Type Nennleistung/Power

EI30/18 2,3 VA

Sicherheitstrafo / Kurzschlußfest

VDE-geprüft 0570 / EN 61558

ENEC10 / UL 506 / CSA

Stoßspannungsgeprüft

Vakuum Epoxidverguss

Temperaturklasse **ta 70° C/B**

Cul-Gewicht: 18 g

Trafo-Gewicht: 115 g

Safety transformer / Short-circuit-proof

VDE-approved 0570 / EN 61558

ENEC10 / UL 506 / CSA



Surge resistance approved

Vacuum Epoxy-Casting

Temperature class **ta 70° C/B**

Cul-Weight: 18 g

Trafo-Weight: 115 g



Ansicht auf Stiftseite - Pin view
Abmessungen - Dimension in mm



Bestell Nr. Order No.	Primär Primary	Sekundär [V] Secondary	Strom [mA] Current	Stiftbelegung Pin	Leerlaufspannung [V] No-Load Voltage ca.	Prüfzeichen / Approvals		
						VDE	UL 1585	UL 506
VN30.18/10533	230V~	6	383	1+5/7+9	10,6	●		●
VN30.18/10534	230V~	9	255	1+5/7+9	14,3	●		●
VN30.18/10535	230V~	12	191	1+5/7+9	19,8	●		●
VN30.18/10536*	230V~	15	153	1+5/7+9	25,4	●		●
VN30.18/10537	230V~	18	127	1+5/7+9	28,4	●		●
VN30.18/10538	230V~	24	95	1+5/7+9	40,0	●		●
VN30.18/10539	230V~	2x 6	2x191	1+5/6+7-9+10	2x10,1	●		●
VN30.18/10540*	230V~	2x 7,5	2x153	1+5/6+7-9+10	2x13,0	●		●
VN30.18/10541	230V~	2x 9	2x127	1+5/6+7-9+10	2x14,4	●		●
VN30.18/10542*	230V~	2x12	2x 95	1+5/6+7-9+10	2x20,5	●		●
VN30.18/10543	230V~	2x15	2x 76	1+5/6+7-9+10	2x25,0	●		●
VN30.18/10972*	230V~	2x18	2x 63	1+5/6+7-9+10	2x28,7			●
VN30.18/10973*	230V~	2x24	2x 47	1+5/6+7-9+10	2x40,5			●
VN30.18/20533*	115V~	6	383	1+5/7+9	10,6			●
VN30.18/20534*	115V~	9	255	1+5/7+9	14,3			●
VN30.18/20535*	115V~	12	191	1+5/7+9	19,8			●
VN30.18/20536*	115V~	15	153	1+5/7+9	25,4			●
VN30.18/20537*	115V~	18	127	1+5/7+9	28,4			●
VN30.18/20538*	115V~	24	95	1+5/7+9	40,0			●
VN30.18/20539*	115V~	2x 6	2x191	1+5/6+7-9+10	2x10,1			●
VN30.18/20540*	115V~	2x 7,5	2x153	1+5/6+7-9+10	2x13,0			●
VN30.18/20541*	115V~	2x 9	2x127	1+5/6+7-9+10	2x14,4			●
VN30.18/20542*	115V~	2x12	2x 95	1+5/6+7-9+10	2x20,5			●
VN30.18/20543*	115V~	2x15	2x 76	1+5/6+7-9+10	2x25,0			●
VN30.18/20972*	115V~	2x18	2x 63	1+5/6+7-9+10	2x28,7			●
VN30.18/20973*	115V~	2x24	2x 47	1+5/6+7-9+10	2x40,5			●

Wirkungsgrad / Efficiency 45 %

Spannungs-Abfall / Voltage drop 60%

* keine Lagerware
VPE 128 Stück pro Karton.

* not available ex stock
Packing unit 128 pieces per box.