

Product name		12VDC Power Adaptor
		<p>Features:</p> <ul style="list-style-type: none"> * 96-264V Wide range input. * DC plug, more convenient to connect. * High efficiency, long service life, high reliability, high cost performance. * Built-in EMI wave filter. * 100% full load burn-in test. * Good automatic protection for over voltage, over current, overload and overheat.
Model	LKS12D2000	
OUTPUT	DC Voltage	12V
	Rated Current	2A
	Current Range	0 ~ 2000mA
	Rated Power	24W
	Ripple & Noise (mv-pp)	Peak to peak voltage(Vpp) <240mV
	No-load Voltage Range	11-13V
	Regulation Accuracy	±10.0%
	Set-up Time	< 1.5S (230VAC input, full load)
	Hold-up Time	> 50mS(230VAC input, full load)
INPUT	Voltage Range	96-264VAC
	Frequency Range	47-63Hz
	Efficiency(Typ.)	> 85%
	AC Input Current (Max.)	< 3A
	Set-up Impulse Current(Typ.)	< 40A @ 230Vac cold start
PROTECTION	Shout Circuit	fuse
ENVIRONMENT	Operating Temp. & Hum.	-10C°~ 50 C°, 20% - 90%RH (non-condensing)
	Storage Temp. & Hum.	- 40C°~ 85 C°, 20% - 95%RH (non-condensing)
SAFETY & EMC	Safety Standards	GB4943, IEC/EN/UL/CSA60950
	Insulation Resistance	I/P-O/P, I/P-FG:100M Ohms / 500VDC / 25 C°/ 70% RH
	EMC IMMUNITY	Compliance to EN61000-4; ENV50204, Grade A light industry standard
OTHERS	Dimension (L*W*H mm)	95* 45* 30
	Packing	in white box
	Cooling	Free Air Convection
	Net Weight (g)	350g